

## Technical Specification

**bz-COR Protective Matte Varnish** is a single-component varnish for indoor use.

### **IMPORTANT:**

Shake the container thoroughly before use. When using the varnish, you must wear a protective mask, and if working in poorly ventilated spaces, be cautious to avoid inhaling product vapors. Drying must take place in a well-ventilated area to ensure an even finish.

Do not use the product if the bp-Cor fixative is not fully dry. Under no circumstances should this product be applied to a damp surface or areas with water residues.

This product is recommended for professional use only.

**KEEP OUT OF REACH OF CHILDREN.**

### **HOW TO USE:**

Shake the varnish well to achieve a uniform consistency. Use only on clean and dry surfaces. This varnish can be applied with a brush, roller, or spray gun, depending on the surface being coated and the desired result. Since the varnish has a matte finish, it is important to stir it during the process to prevent particles from settling unevenly.

**INDOOR USE:** 2 coats. Allow 4-5 hours of drying time between coats.

### **APPLICATION TEMPERATURE:**

We recommend using bz-Cor Nature Matt varnish at a temperature of no lower than 10°C and no higher than 30°C. Temperatures outside this range may cause excessively fast drying or an uneven finish.

### **STORAGE:**

Store the product in a sealed container in a cool, well-ventilated place, avoiding direct sunlight. Shelf life: 12-15 months. After use, ensure the product is well sealed and not exposed to air for extended periods. Before using again, turn the container upside down for a few minutes, then shake well before application.

### **COVERAGE:**

One liter of product covers approximately 8 square meters per coat.

### **DRYING TIME:**

Each coat requires 2-3 hours of drying time. The final coat should be left to dry for 24 to 48 hours, with maximum durability achieved after 7 days.